

# Infrared Cameras

Security



The Security You Need.

The Security You Deserve.



## → Features

- ▶ Night Vision Waterproof
- ▶ Integrative Camera
- ▶ 1/4" Sharp CCD Image Sensor
- ▶ 420 TV Lines
- ▶ Infrared Lamp Auto Switch

## → Specifications

Image Device	1/4-inch Sharp CCD imagesens
Effective Picture elements	PAL 500(H)×582 (V) NTSC 510(H)×492 (V)
Sensing Area	4.9mm×3.7mm
System Of Signal	PAL/NTSC
Horizontal Resolution	420 TV Lines (H)
Lens Mount	3.6mm
S/N Ratio	More than 48 db
Minimum illumination	Color 1LUX/IR 0 LUX
IR terms	Illumination < 0.8LUX , CDS Auto open
Video Output	1.0V(P-P)75 Ω
Power Supply	DC12V
Operating Current	180mA
Video Output Connector	BNC
Infrared Wave length	12 units 850nm
Infrared Lamps Irradiation Distance	10m
Infrared Lamps Auto Switch	Night(on)/Day(off)
Time piece frequency	NTSC:19.0699,PAL:19.3125
Scanning frequency	2:1scan interleaved
Video output	1VPP , 75 OHMS
Gamma Identity	0.45
Size	63Dmm*49Hmm
Weight	185g
Deposited temperature	-30° -+60°
Working temperature	-10° -+45°

Night Look 12