

Hidden Camera Smoke Detector



Security

The Security You Need.
The Security You Deserve.



→ Key Features

- ▶ High- Resolution
- ▶ For small simple monitoring applicaion
- ▶ Internal synchronizaion
- ▶ Smoke detector does not function
- ▶ Auto electric shutter
- ▶ Variety lens open
- ▶ Easy to install, easy to use

→ Specifications

Image Device	1/4" Color CCD Sensor Interline
Effective Picture Elements	NTSC 768(H) X 494(V) PAL 752(H) X 582(V)
Scanning System	NTSC/EIA Standard 525 lines, 30 frames/sec PAL/CCIR standard 625 lines, 25 frames/sec
Synchronizing	Internal
Horizontal Resolution	More than 460 TV Lines
Electronic Shutter Conrol	Auto-Electronic shutter (1/60-1/100000)NTSC/EIA (1/50-100000) PAL/CCIR
Gamma	.045
Minimum illumination	2 Lux/F1.2
Video output	1Vp-p /75 Ohms, composite
Video S/N ratio	46db (AGC off)
White Balance	Auto-white balance (2000K-10000K)
Operating Temperture	-10C-50C
Storage Temperture	-30C-80C
Power Requirement	DC 12V + 1.2Vdc
Power Comsumption	DC 12V typical 150mA
Dimensions	130(0) 57(H) mm
Weight	280 g
Lens	STD: 3.6mm Options: 2.9/ 4.3/6.0/8.0/12.0mm
Shipping	1.5'/Kg; 20pcs/ carton

TCD-23B9